



PRO EPOXY

COLOR EPOXY GROUT & MORTAR



- ◆ HIGH CHEMICAL RESISTANCE
- ◆ GREAT FOR HYGIENIC AND FOOD-PROCESSING SPACES
- ◆ NONFLAMMABLE
- ◆ EASY WORKABILITY
- ◆ WATER CLEANABLE BEFORE CURING



PRO EPOXY

MERKRETE PRO EPOXY is a three-component, 100%-solids epoxy compound developed for sanitary applications. Pro Epoxy is used for setting and grouting ceramic and quarry tile, pavers and mosaics on horizontal and vertical surfaces. It is an excellent setting material for moisture-sensitive and resin-backed stones like black, red and green marbles. Pro Epoxy is used in commercial breweries, dairies, food-processing facilities, distilleries, residential kitchens and bathrooms. It produces a high-strength mortar that is stain resistant, impermeable and shock resistant.

USES:

- Setting moisture-sensitive and resin-backed stones
- Hygienic and chemical-contact installations
- Completely waterproof installations like tile tubs, showers and swimming pools

STANDARDS:

- ANSI A108.6 and A118.3

SUITABLE SUBSTRATES:

- Cement Tile
- Ceramic Mosaic
- Quarry Tile
- Paver

PRO EPOXY GROUT COVERAGE CHART

Sq. Ft. per Gallon	Joint Width		
Mosaics	Joint Width		
	1/8"	1/4"	3/8"
1" x 1" x 3/16"	40	23	18
2" x 2" x 1/4"	56	30	22
2" x 2" x 1/4"	107	56	39
Wall Tile	Joint Width		
	1/8"	1/4"	3/8"
4 1/4" x 4 1/4" x 5/16"	91	47	32
6" x 6" x 1/4"	158	81	56
Floor Tile	Joint Width		
	1/8"	1/4"	3/8"
4' x 8" x 1/2"	70	36	25
6" x 6" x 3/8"	105	54	37
6" x 6" x 1/2"	79	40	28
8" x 8" x 3/8"	140	71	48
12" x 12" x 3/8"	208	105	71
12" x 12" x 1/2"	156	79	53
12" x 12" x 5/16"	250	127	86
13" x 13" x 3/8"	225	114	77
16" x 16" x 3/8"	276	140	94
18" x 18" x 3/8"	311	157	105
20" x 20" x 3/8"	345	174	117



PRO EPOXY SETTING COVERAGE CHART

Trowel Size	$\frac{3}{16}$ " x $\frac{1}{4}$ " V-Notch	$\frac{3}{16}$ " x $\frac{1}{4}$ " Square Notch
Sq. Ft. per Gallon	36	22

ORDERING INFORMATION

Color	Pro Epoxy Commercial Kit (2-gal. pail)	Pro Epoxy Part C (Colored Sand) (11-lb. box)	Pro Epoxy Parts A & B (1-gal. pail)
			1842
NAVAJO WHITE	1841-00012	1843-00012	
BONE	1841-00017	1843-00017	
CREAM	1841-00018	1843-00018	
CANVAS	1841-00021	1843-00021	
CHAMOIS	1841-00024	1843-00024	
TUMBLEWEED	1841-00025	1843-00025	
SILVER	1841-00030	1843-00030	
LIGHT TAUPE	1841-00032	1843-00032	
RIVER ROCK	1841-00034	1843-00034	
NATURAL GRAY	1841-00035	1843-00035	
GRAY	1841-00038	1843-00038	
CARMEL	1841-00063	1843-00063	
SANDSTONE	1841-00071	1843-00071	
MOCHA	1841-00145	1843-00145	
SANTA FE	1841-00150	1843-00150	
BUCKSKIN	1841-00153	1843-00153	
TRUE TAUPE	1841-00162	1843-00162	
COCO	1841-00178	1843-00178	
TERRACOTTA	1841-00191	1843-00191	
BLACK SAPPHIRE	1841-00525	1843-00525	

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424