



UNDERLAY RS

MORTAR BED
UNDERLAYMENT



- ◆ 1/8" – 3" THICKNESS FOR RAMPING, PATCHING AND SCREEDING
- ◆ CREAMY, TROWELABLE TEXTURE MINIMIZES SANDING
- ◆ FAST SETTING — 6 TO 8 HOURS BEFORE FLOORING OVERLAY
- ◆ 3,500 PSI HARDNESS — PERFECT FOR RETAIL AND LIGHT COMMERCIAL



UNDERLAY RS MORTAR BED UNDERLAYMENT

UNDERLAY RS is a fast-setting, troweled polymer-modified underlayment designed to provide a suitable surface for floor coverings such as vinyl, resilient tile, carpet, ceramic and stone tile. It is ideal for ramping, patching and screed applications.

USES:

- 1/8" – 3" for ramping, patching and screeding
- Rapid formula perfect for remodel construction — 6- to 8-hour cure
- Low prep — reduces labor/time

SUITABLE UNDERLAYMENT:

- Substrate for floor covering

SUITABLE SUBSTRATES:

- Mortar Beds
- Ceramic Tile & Stone
- Concrete
- Concrete Masonry
- Exterior-grade plywood (interior applications)

APPROXIMATE COVERAGES

Thickness	Min. Coverage	Max Coverage
1/8"	44 sq. ft	47 sq. ft
1/4"	22 sq. ft	24 sq. ft
1/2"	11 sq. ft	12 sq. ft
1"	6 sq. ft	6 sq. ft

ORDERING INFORMATION

Item#	Size
1885	50-lb. bag

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424