



HYDRO GUARD SP-1



- ◆ DRIES FASTER THAN TYPICAL WATERPROOFING PRODUCTS
- ◆ WATER AND VAPOR PROOF
- ◆ WATER (FLOOD) TEST AFTER 4 – 6 HOUR CURE
- ◆ ANTI-FRACTURE PROTECTION UP TO 1/8" (3 MM)
- ◆ EXCEEDS ANSI A118.10 AND A118.12



HYDRO GUARD SP-1



Merkrete Hydro Guard SP-1 is a fast-drying, thin, load-bearing waterproof and crack isolation membrane composed of modified elastomeric copolymers. With excellent elongation, adhesion and strength properties, Hydro Guard SP-1 provides a 100% waterproof membrane that limits the transfer of substrate cracks to the finished ceramic or stone tile surface. Hydro Guard SP-1 is installed in a liquid state and can be applied to practically any form or irregular shape forming a monolithic waterproof barrier.

STANDARDS:

- Exceeds ANSI A118.10 and A118.12
- IAPMO approved

USES:

- Interior and exterior
- Swimming pools, fountains and water features
- Shower pans, stalls and tubs surrounds
- Industrial, commercial and residential bathrooms
- Spas and hot tubs
- Kitchens and food processing areas
- Terraces and balconies over unoccupied spaces

SUITABLE SUBSTRATES:

- Brick masonry
- Cement backer board¹
- Cement mortar beds
- Cement plaster
- Cement terrazzo
- Ceramic tile and stone
- Concrete
- Concrete masonry
- Exterior grade plywood²
- Gypsum wallboard²
- Gypsum mortar bed³
- Oriented strand board²

¹ Consult cement backer board manufacturer for installation recommendations and to verify acceptability for exterior use.

² Interior use only.

³ Requires use of 101 Overspray Primer

APPROXIMATE COVERAGE:

- 50 sq. ft. per 1 gallon

PAREXUSA

Parex USA, Inc., a California Corporation

Corporate Office

2150 Eastridge Ave • Riverside, CA 92507

merkrete.com • 866-516-0061

Tech Support: 800-226-2424

ORDERING INFORMATION	
Item No.	Size
1806	1 Gal
3793	3.5 Gal
1807	5 Gal